

AYDINDISPLAYS

WWW.AYDINDISPLAYS.COM | SALES@AYDINDISPLAYS.COM



MODEL 8819SD

*19" RUGGED COTS
SMART DISPLAY FOR
DEFENSE APPLICATIONS*

FEATURES:

- Sealed, Fanless Design
- High Brightness LED Backlight
- Resistive Touch
- Full Dimming Range
- AR Window
- Integrated PC Supporting Windows or Linux

OPTIONS:

- 28 VDC
- Fiber Ethernet

Aydin is:



7/20_Rev 12

1 Riga Lane,
Birdsboro, PA
19508, U.S.A.,
1-866-367-2934

SPECIFICATIONS:

Display Type:	19" TFT Active Matrix LCD
Active Display Area:	15.02" x 12.135"
Pixel Pitch:	0.294 x 0.294 mm
Brightness:	Standard: 550cd/m ² 400 cd/m ² (with touch)
Viewing Angle:	±80° All directions
Contrast Ratio:	1000:1
Response Time:	25 ms (Typical)
Display Colors:	16 Million
Native Resolution:	1280 x 1024
Processor:	i7-8800H 2.6 (4.3) GHZ STD Customizable with Type 6 Com Express Processor Modules
Memory:	32GB of Dual Channel DDR4 memory
Storage:	1TB removable SSD with SATA III Transfer speed
I/O Ports:	(2) USB-standard type A non-MIL (backwards compatible with 2.0 + 1.1) (1) USB-A MIL Type (2) GB Ethernet (copper/copper)
OS Support:	Windows Compatible, Linux
Display Controls:	Soft Power, Brightness

Designed To Meet:

Temperature:	Operating: 0° C to 50° C, MIL-STD-810G Method 501/502, Procedure II Storage: -20° C to +60° C, MIL-STD-810G Method 501/502, Procedure I
Humidity:	Operating: 5 to 95% RH Non- condensing MIL-STD-810G, Method 507 Procedure I
Altitude:	Operating: Up to 42,000 ft. above sea level Storage: Up to 54,000 ft. above sea level MIL-STD-810G, Method 500
Shock:	MIL-S-901D Grade A Class I Type A
Vibration:	MIL-STD-167-1A Type I
Drip:	IP 65 Rating MIL-STD-810G, Method 506.5, Procedure III
Sand/Dust:	MIL-STD-810G, Method 510.5, Procedure I & III
EMI:	MIL-STD-461F, CE101, CE102, RE101, RE102, CS101, CS114, CS116, RS101
Power:	Supply: 80-275 VAC, Auto Ranging Frequency: 47-63 Hz Power: 105 Watts (Typical) Chassis Connector: MS3476L8-33S (DC) or MS3102R10SL-3P (AC) Cable Connector: MS3476L8-33S (DC) or MS3106R10SL-3S (AC)
Dimensions:	18.97"W x 15.72"H x 4.34" DP
Weight:	31 lbs

All specifications subject to change without notice.

7/20_Rev 12

WWW.AYDINDISPLAYS.COM | SALES@AYDINDISPLAYS.COM

Please contact your sales representative for more information.
Consult Factory on pricing and lead time.